



SnapBrite S100-3W-12E

LOW VOLTAGE AC LED MODULE

3 Watt 227lm 12V AC

LOW VOLTAGE DIMMABLE LINEAR MODULE

Technical Data Sheet





Direct Connect AC LED lighting technology

SnapBrite™ S100-3W-12E

Description

SnapBrite low voltage AC LED modules are fast, easy and reliable LED light sources for lighting OEMs in need of LED solutions that offer direct low voltage connectivity with a 12V AC electronic transformer.

Lynk’s patented AC LED technology eliminates the requirement for an expensive, bulky and failure prone AC – DC power supply or driver. Delivering efficiency, reliability and a high power factor, SnapBrite modules can be used by lighting manufacturers in many types of fixture as an effective replacement for energy hungry incandescent, Xenon or Halogen lamps. Additionally, the modules will dim with many popular leading and trailing edge phase cut dimmers designed for use with electronic transformers.

Look for the Lynk Labs name or this private label mark to ensure you are always backed by Lynk Labs high quality AC LED technology, IP, and reliability. Lynk Labs - Your AC LED Experts!



Features

- Lower Cost & Increased Reliability with AC LEDs
- No Drivers - Operates directly with Low Voltage Electronic Transformers
- Dimmable - Works with most existing AC Dimmers
- High Power Efficiency
- High Power Factor
- Significant Energy Savings
- Long Operating Life
- Reliable, Fast & Easy

Applications

- Linear Lighting
- Cove Lighting
- Under Cabinet Lights
- Step Lights
- Accent Lights
- Garden Lights
- Display Lights



Contents:


1. Description, Features and Applications	2
2. Contents	3
3. Mechanical Dimensions	4
4. Electrical & Optical Characteristics	5
5. Absolute Maximum Ratings	5
6. C.I.E. Chromaticity Coordinates	6
7. Typical Electrical & Optical Characteristic Curves	9
8. Part Number Identification.....	12
9. Packaging	13
10. Reliability and Average Lumen Maintenance	13
11. Design Considerations/Specifications.....	13



3. Mechanical Dimensions

Linear LED Assembly

S100EP2HT03WXXKXS-12E	Length	Width	Height
Size in Millimeters	100 mm	10 mm	2 mm
Tolerance	+/- 0.254mm	+/- 0.254mm	+/- 10%



Notes :

1. All dimensions are in millimeters.
2. Tolerance is $\pm 0.05\text{mm}$ unless otherwise noted.



4. Electrical & Optical Characteristics

ITEM	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Drive Voltage	V _f	12V AC	V _{rms}	7	12	13
Viewing Angle	2θ _½		deg		120	
Thermal Resistance	R _{θj-c}	I _f =267 mA _{rms}	°C/W		tba	
Typical Operating Power	W _T	I _f =267 mA _{rms}	W		3.2	
Luminous Flux (3000K CRI80)	Φ	V _f =12 V _{rms}	lm		227	
Luminous Efficacy (3000K)	η _v	V _f =12 V _{rms}	lm/w		71	

*Measurement Uncertainty of the Luminous Flux: ± 10%

*Values given are for specified drive current/voltage at 25°C ambient temperature

MODEL NUMBER	CCT	CRI	VAC	POWER	LUMEN	lm/W
S100EP2HT03W27KXS-12E	2700K	80	12	3.2	225	70
S100EP2HT03W30KXS-12E	3000K	80	12	3.2	227	71
S100EP2HT03W40KXS-12E	4000K	80	12	3.2	234	73

Other CCTs & 90 CRI Option may be Available to Special Order


5. Absolute Maximum Ratings (@ Ta=25°C)

ITEM	SYMBOL	ABSOLUTE MAXIMUM RATING	UNIT
Power Dissipation	P _d	6	W
A.C. Current	I _f	500	mA _{rms}
AC Voltage	V _f	13	V
Operating Temperature	T _o	-25 ~ +100	°C
Storage Temperature	T _s	-40 ~ +100	°C
Soldering Temperature(Hand)	T _{sld}	370	°C



6. CIE Chromaticity Coordinates

White Binning Structure Graphical Representation




White Bin Structure

Bin Code	x	y	Typ. CCT (K)	Bin Code	x	y	Typ. CCT (K)
V1	0.346	0.369	4870	W1	0.329	0.354	5475
	0.355	0.376			0.338	0.362	
	0.353	0.362			0.337	0.349	
	0.345	0.356			0.329	0.342	
V4	0.345	0.356	4870	W4	0.329	0.342	5475
	0.353	0.362			0.337	0.349	
	0.352	0.349			0.337	0.337	
	0.344	0.343			0.329	0.331	
V2	0.338	0.362	5155	W2	0.321	0.346	5830
	0.346	0.369			0.329	0.354	
	0.345	0.356			0.329	0.342	
	0.337	0.349			0.322	0.335	
V3	0.337	0.349	5155	W3	0.322	0.335	5830
	0.345	0.356			0.329	0.342	
	0.344	0.343			0.329	0.331	
	0.337	0.337			0.322	0.324	

- Tolerance on each color bin (x , y) is ± 0.01



Neutral White Binning Structure Graphical Representation




Neutral White Bin Structure

Bin Code	x	y	Typ. CCT (K)	Bin Code	x	y	Typ. CCT (K)
S1	0.387	0.396	3825	S2	0.374	0.387	4100
	0.401	0.404			0.387	0.396	
	0.395	0.388			0.382	0.380	
	0.382	0.380			0.370	0.373	
S4	0.382	0.380	3825	S3	0.370	0.373	4100
	0.395	0.388			0.370	0.373	
	0.390	0.372			0.382	0.380	
	0.378	0.365			0.378	0.365	
S0	0.374	0.369	3975		0.367	0.358	
	0.378	0.384			0.374	0.369	
	0.391	0.392			0.378	0.384	
	0.386	0.376			0.391	0.392	

- Tolerance on each color bin (x , y) is ± 0.01



Warm White Binning Structure Graphical Representation



Warm White Bin Structure


Bin Code	x	y	Typ. CCT (K)	Bin Code	x	y	Typ. CCT (K)
N1	0.443	0.421	2950	N2	0.430	0.417	3150
	0.456	0.426			0.443	0.421	
	0.447	0.408			0.435	0.403	
	0.435	0.403			0.422	0.399	
N4	0.435	0.403	2950	N3	0.435	0.403	3150
	0.447	0.408			0.422	0.399	
	0.437	0.389			0.426	0.385	
	0.426	0.385			0.415	0.381	
N0	0.424	0.392	3050				
	0.432	0.410					
	0.445	0.414					
	0.436	0.396					

- Tolerance on each color bin (x , y) is ± 0.01




7. Typical Electrical & Optical Characteristic Curves
With ballast Resistor


Relative Power vs Voltage



Relative Luminous Flux vs. Voltage




Lumen Thermal de-rating curve







1. White




2. Neutral White



3. Warm White







8.Part Number Identification

04/08/2014

Part Number											
Product Code	Shape	Dimension/Diameter (mm)	Internal Codes	Module Power	aTHD	CCT (XXX) Warm on Dim (XYWD)	Connection Type	CRI	Input Voltage	Miscellaneous	Revision Level

S 1 0 0 E P 2 H H 0 3 W S 3 0 K X S 1 2 E , R1

Model Number											
Product Code	Shape	Dimension/Diameter	LED Indicator	Module Power	aTHD	CCT (XXX) Warm on Dim (XYWD)	Connection Type	CRI	Input Voltage	Miscellaneous	

S 1 0 0 0 3 W S 3 0 K x S 1 2 E

Product Code	
S	= SnapBrite™
T	= Tesla™
G	= GeoLite™
B	= BriteDriver®

Shape	
R	= Round
S	= Square
T	= Star
L	= Linear

Dimension/Diameter		
L	=	X X X
W	=	Y Y Y
D	=	Z Z Z

Module Power	
Q	= 0.25W
H	= 0.5W
T	= 0.75W
R	= Decimal Point

aTHD	
L	= < 20%
S	= ≥ 20%

Miscellaneous	
	Customer Code
	Special Design
	Special Silk Scn
	TBA

CCT/WOD				
2	2	K		= 2200K
2	7	K		= 2700K
3	0	K		= 3000K
3	5	K		= 3500K
4	0	K		= 4000K
5	0	K		= 5000K
5	7	K		= 5700K
3	2	W	D	= ~ 2700K To 2200K Warm on Dim
4	2	W	D	= ~ 3000K To 2200K Warm on Dim
5	2	W	D	= ~ 3500K To 2200K Warm on Dim

Connection Type	
C	= Poke-In Connector
I	= Insulation Displacement Connector
O	= Connector + Solder Pads
W	= Wire "Pigtail"
X	= Solder Pads

CRI	
L	= < 80 CRI
S	= ≥ 80 CRI
H	= ≥ 90 CRI

Revision Level	
P1 to 9	Prelim
R1 to ∞, R1s	
	TBA

LED Indicator	
P	Prolite
E	EverLite
D	Interlight
C	Citizen
S	SemiLeds
N	Nichia
...	TBA

Input Voltage	
12V	= 12 VAC, Magnetic or Electronic Transformer Source
12E	= 12 VAC, Electronic Transformer Source Only
120V	= 120 VAC
120R	= Rectified 120 VAC
230V	= 230 VAC



9. Packaging

LED Modules will be packaged in trays for primary protection.

According to the total delivery amount, cardboard boxes will be used to protect the Trays of LED Modules from mechanical shocks during transportation.

The boxes are not water resistant and therefore must be kept away from water and moisture.

10. Reliability and Average Lumen Maintenance

Before releasing new products the manufacturer puts a representative product sample set through an entire suite of qualification tests, including the most stressful test for high power LEDs, the Wet High-Temperature Operating Life (WHTOL) test at 85°C/85%RH for 1000 hours at the specified operating current.

LED lifetime has been extrapolated based on the accumulated operating and accelerated aging data. Based on this data, the manufacturer projects that the LED products will deliver, on average, 70% lumen maintenance at 50,000 hours of operation at the specified operating current, provided that the case temperature is maintained at or below 80°C.

11. Design Considerations/Specifications

11.1 Thermal Management Requirements

- a. Heat Sink Required (22 square cm/watt surface area)
- b. Thermal epoxy – No mechanical mounting required
- c. Thermal tape – No mechanical mounting required
- d. Thermal grease – Mechanical mounting required

11.2. Mechanical Mounting

- a. Use nylon washers for all mounting holes when using screws.
- b. Do not put force on LEDs.
- c. Do not bend PCB.

11.3. Electrical Interface

Solder Pads

11.4. Moisture Sensitivity

The module can operate for up to 1000hrs at 85 °C and 65% Relative Humidity.

It is not designed for operation in wet conditions without an additional conformal coating which must be approved and supplied by the manufacturer during the module build process or warranty will be voided.