



GeoLite®
24V AC LED Festoon
GF075WPXXXKS-24
0.75W 24V AC

Product Data Sheet





Direct Connect AC LED lighting technology

GeoLite® GF075WPXXXWDS -24

Description

GeoLite low voltage AC LED Festoon is a fast, easy and reliable LED light source for lighting OEMs in need of LED solutions that offer direct low voltage connectivity with a 24V AC magnetic or BriteDriver electronic transformer.

Lynk's patented AC LED technology eliminates the requirement for an expensive, bulky and failure prone AC – DC power supply or driver. Delivering efficiency, reliability and a high power factor, GeoLite tape can be used by lighting manufacturers in many types of fixture as an effective replacement for energy hungry incandescent, Xenon or Halogen lamps. Additionally, the modules will dim with many popular leading and trailing edge phase cut dimmers designed for use with proper magnetic and BriteDriver electronic transformers.

Look for the Lynk Labs name or this private label mark to ensure you are always backed by Lynk Labs high quality AC LED technology, IP, and reliability. Lynk Labs - Your AC LED Experts!



Features

- Lower Cost & Increased Reliability with AC LEDs
- No Drivers - Operates directly with Low Voltage Electronic Transformers
- Dimmable - Works with most existing AC Dimmers
- High Power Efficiency
- High Power Factor
- Significant Energy Savings
- Long Operating Life
- Reliable, Fast & Easy

Applications

- Linear Lighting
- Cove Lighting
- Under Cabinet Lights
- Step Lights
- Accent Lights
- Garden Lights
- Display Lights

Contents:

1. Description, Features and Applications2

2. Contents 3

3. Mechanical Dimensions4

4. Electrical & Optical Characteristics..... 4

5. Absolute Maximum Rating.....5

6. Powering Specifications 5

.



3. Mechanical Dimensions

GF075WPXXXKS-12	Length	Width	Height
Size in millimeters	44.5 mm	12.7 mm	12.7 mm
Size in inches	1.75"	0.5"	0.5"

4. Electrical & Optical Characteristics

ITEM	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Drive Voltage	V _f	12V AC	V _{rms}	14	24	26
Viewing Angle	2θ _{1/2}		deg		140	
Typical Operating Power	W _T	I _f =32 mA _{rms}	W		0.75	
Luminous Flux (42WD) /m	Φ	V _f =24 V _{rms}	lm		60	
Luminous Efficacy (42WD)	η _v	V _f =24 V _{rms}	lm/w		80	

*Measurement Uncertainty of the Luminous Flux: ± 10%

*Values given are for specified drive current/voltage at 25°C ambient temperature

MODEL NUMBER	CCT	CRI (full on)	VAC	POWER	LUMEN	lm/W	LENS
GF075WPC27KS-24	2200K	80	24	0.75	60	80	Clear
GF075WPF27KS-24	2200K	80	24	0.75	60	80	Frosted
GF075WPC30KS-24	3000K	80	24	0.75	60	80	Clear
GF075WPF30KS-24	3000K	80	24	0.75	60	80	Frosted
GF075WPC40KS-24	4000K	80	24	0.75	60	80	Clear
GF075WPF40KS-24	4000K	80	24	0.75	60	80	Frosted



5. Absolute Maximum Ratings (@ Ta=25°C)

ITEM	SYMBOL	ABSOLUTE MAXIMUM RATING	UNIT
Power Dissipation/ m	Pd	1.1	W
A.C. Current	If	55	mA _{rms}
AC Voltage	Vf	26	V
Operating Temperature	To	-25 ~ +75	°C
Storage Temperature	Ts	-40 ~ +100	°C
Soldering Temperature(Hand)	Tsld	370	°C

6. Powering Specification

Power Supply/Driver	Output RMS	Frequency	Minimum	Dimming
BriteDriver™ (Recommended)	23.4 VAC	60/44k Hz	1 Watt	Phase Cut
12 VAC Magnetic	24 VAC	50/60 Hz	5 Watt	Phase Cut

Warning – Do Not Power SnapBrite Festoon with more than 24V AC. Use only with Lynk Labs' BriteDriver™ AC LED Power Supplies or other approved transformers. Any Exceptions Void all warranties. Contact Lynk Labs for details and approvals.